

Supplementary Material for “BIRNAT: Bidirectional Recurrent Neural Networks with Adversarial Training for Video Snapshot Compressive Imaging”

Ziheng Cheng¹[0000-0002-7504-197X], Ruiying Lu¹[0000-0002-8825-6064],
Zhengjue Wang¹[0000-0002-1846-495X], Hao Zhang¹[0000-0002-2928-2692],
Bo Chen^{1*}[0000-0001-5151-9388], Ziyi Meng^{2,3}[0000-0001-8294-8847], and
Xin Yuan^{4*}[0000-0002-8311-7524]

¹ National Laboratory of Radar Signal Processing, Xidian University, Xi'an, China

² Beijing University of Posts and Telecommunications, Beijing, China

³ New Jersey Institute of Technology, NJ, USA ⁴ Nokia Bell Labs, NJ, USA

zhcheng@stu.xidian.edu.cn,

{ruiyinglu_xidian,zhengjuewang,zhanghao_xidian}@163.com,

bchen@mail.xidian.edu.cn,mengziyi@bupt.edu.cn,xyuan@bell-labs.com

1 Experiment Settings

The details of network architecture for BIRNAT is shown in Fig.1 (Fig. 3 in the main paper, reproduced here) and Table 1, where the output size corresponds to a mini-batch, and the activation function is LeakyReLU. As displayed in the table, the ‘*conv.*’ refers to the convolutional operation and ‘*deconv.*’ denotes the deconvolutional operations, and a ‘*resblock*’ represents three two-layer convolutional layers with three residual connections. Moreover, the architecture of forward RNN is the same as backward RNN, while the parameters are not shared.

The details of our repurposed U-net architecture in the experiment is shown in Fig. 2.

* corresponding author.




Fig. 1. Details of BIRNAT. C denotes concatenation along the 3rd (temporal) dimension. The numbers in the AttRes-CNN and RNN cell denote the numbers of channels in each feature map.




Fig. 2. The network architecture of the U-net in our experiments.

Table 1. Network architecture for the BIRNAT

Module	Operation	Kernel	Stride	Output Size	
cnn1	conv.	5×5	1	$256 \times 256 \times 16$	
	conv.	3×3	1	$256 \times 256 \times 32$	
	conv.	1×1	1	$256 \times 256 \times 32$	
	conv.	3×3	2	$128 \times 128 \times 128$	
cnn2	deconv.	3×3	2	$256 \times 256 \times 32$	
	conv.	3×3	1	$256 \times 256 \times 32$	
	conv.	1×1	1	$256 \times 256 \times 16$	
	conv.	3×3	1	$256 \times 256 \times 1$	
cnn3	conv.	5×5	1	$256 \times 256 \times 20$	
	conv.	1×1	1	$256 \times 256 \times 40$	
	conv.	3×3	1	$256 \times 256 \times 40$	
	conv.	1×1	1	$256 \times 256 \times 40$	
	conv.	3×3	1	$256 \times 256 \times 40$	
	conv.	3×3	1	$256 \times 256 \times 20$	
cnn4	conv.	5×5	1	$256 \times 256 \times 20$	
	conv.	1×1	1	$256 \times 256 \times 40$	
	conv.	3×3	2	$128 \times 128 \times 40$	
	conv.	1×1	1	$128 \times 128 \times 40$	
	conv.	3×3	1	$128 \times 128 \times 40$	
	deconv.	3×3	2	$256 \times 256 \times 10$	
cnn5	conv.	3×3	1	$256 \times 256 \times 40$	
	conv.	1×1	1	$256 \times 256 \times 40$	
	conv.	3×3	1	$256 \times 256 \times 40$	
	conv.	1×1	1	$256 \times 256 \times 40$	
	conv.	3×3	1	$256 \times 256 \times 20$	
	conv.	3×3	1	$256 \times 256 \times 20$	
cnn6	conv.	3×3	1	$256 \times 256 \times 40$	
	conv.	1×1	1	$256 \times 256 \times 40$	
	conv.	3×3	1	$256 \times 256 \times 40$	
	conv.	1×1	1	$256 \times 256 \times 40$	
	conv.	3×3	1	$256 \times 256 \times 20$	
	conv.	1×1	1	$256 \times 256 \times 1$	
resblock1	$3 \times \text{resblock}$	<div><div>3×3</div><div>3×3</div></div>	$\times 3$	1	$128 \times 128 \times 128$
resblock2	$2 \times \text{resblock}$	<div><div>3×3</div><div>3×3</div></div>	$\times 3$	1	$256 \times 256 \times 50$
self-attention	\boldsymbol{w}_1	1×1	1	$128 \times 128 \times 16$	
	\boldsymbol{w}_2	1×1	1	$128 \times 128 \times 16$	
	\boldsymbol{w}_3	1×1	1	$128 \times 128 \times 128$	

2 More Experimental Results

We show additional experimental results of the proposed framework on the simulated data and real data captured by SCI cameras. As a further illustration of the results shown in the main paper, we show the whole reconstructed frames of **Kobe**, **Traffic**, **Runner**, **Drop**, **Aerial** and **Vehicle** using four different methods compared with ground truth from Fig.3 to Fig.24.

We also show the reconstructed images using four different methods on the real data **Wheel**, **Handlen**, **Duominuo** and **Water Balloon** from Fig.25 to Fig.28.




Fig. 3. Ground truth for Kobe.




Fig. 4. Reconstructed results by our proposed BIRNAT for Kobe, PSNR: 32.71, SSIM: 0.9316.




Fig. 5. Reconstructed results by GAP-TV for Kobe, PSNR: 26.45, SSIM: 0.8448.




Fig. 6. Reconstructed results by DeSCI for Kobe, PSNR: 33.25, SSIM: 0.9518.




Fig. 7. Reconstructed results by U-net for Kobe, PSNR: 27.79, SSIM: 0.8071.



Fig. 8. Ground truth for Traffic.



Fig. 9. Reconstructed results by our proposed BIRNAT for **Traffic**, PSNR: 29.33, SSIM: 0.9322.



Fig. 10. Reconstructed results by GAP-TV for **Traffic**, PSNR: 20.89, SSIM: 0.7148.



Fig. 11. Reconstructed results by DeSCI for **Traffic**, PSNR: 28.72, SSIM: 0.9250.



Fig. 12. Reconstructed results by U-net for **Traffic**, PSNR: 24.62, SSIM: 0.8403.




Fig. 13. Ground truth and reconstructed results by different methods on **Runner**. PSNR and SSIM: 28.81, 0.9092 (GAP-TV); 38.76, 0.9693 (DeSCI); 34.12, 0.9471 (U-net); 38.70, 0.9685 (our proposed BIRNAT).




Fig. 14. Ground truth and reconstructed results by different methods on **Drop**, PSNR and SSIM: 34.74, 0.9704 (GAP-TV); 43.22, 0.9925 (DeSCI); 36.56, 0.9494 (U-net); 42.28, 0.9896 (our proposed BIRNAT).




Fig. 15. Ground truth for Aerial.




Fig. 16. Reconstructed results by our proposed BIRNAT for *Aerial*, PSNR: 28.99, SSIM: 0.9136.




Fig. 17. Reconstructed results by GAP-TV for *Aerial*, PSNR: 25.05, SSIM: 0.8281.




Fig. 18. Reconstructed results by DeSCI for Aerial, PSNR: 25.33, SSIM: 0.8603.




Fig. 19. Reconstructed results by U-net for Aerial, PSNR: 27.18, SSIM: 0.8690.



Fig. 20. Ground truth for Vehicle.



Fig. 21. Reconstructed results by our proposed BIRNAT for `Vehicle`, PSNR: 27.84, SSIM: 0.9092.




Fig. 22. Reconstructed results by GAP-TV for `Vehicle`, PSNR: 24.82, SSIM: 0.8383.



Fig. 23. Reconstructed results by DeSCI for `Vehicle`, PSNR: 27.04, SSIM: 0.9094.



Fig. 24. Reconstructed results by U-net for `Vehicle`, PSNR: 26.43, SSIM: 0.8817.




Fig. 25. The results of different methods on real data **Wheel**.




Fig. 26. The results of different methods on real data **Handlen**.




Fig. 27. The results of different methods on real data for Domino.




Fig. 28. The results of different methods on real data Water Balloon.